SECTION 1 : IDENTIFICATION

Product identifier used on the label:			
Product Name:	BRONZE ALLOYS XP55, C61550, C69300, C66540		
SDS Manufacturer Number:	226999		
Other means of identification:			
Recommended use of the chemical and restrictions on use:			
Chemical manufacturer address and telephone number:			
Manufacturer Name:	PMX Industries, Inc.		
Address:	5300 Willow Creek Drive SW Cedar Rapids, Iowa 52404-4303 USA		
General Phone Number:	319-368-7700		
General Fax Number:	319-368-7701		

Emergency phone number: Emergency Phone Number:

319-368-7700

SECTION 2 : HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Signal Word:	Not applicable.	
GHS Class:	Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200	
Hazards not otherwise classified that have been identified during the classification process:		
Emergency Overview:	Copper alloy products in the natural state do not present a hazard for emergency response personnel.	
Route of Exposure:	Inhalation, Eye Contact, Skin Contact	
Potential Health Effects:	Copper alloy products in the natural state do not present an inhalation, ingestion, or contact hazard. However, operations such as burning, welding, sawing, brazing, or grinding may release fumes and/or dusts which may present health hazards if occupational exposure limits are exceeded.	
Eye:	Short-term exposure to fumes/dust may produce irritation.	
Skin:	Repeated or prolonged exposure to copper dusts or mists may cause irritant or allergic contact dermatitis.	
Inhalation:	Short-term exposure to fumes/dust may produce irritation of the respiratory system. Exposure to high concentrations of copper oxide fumes may cause metal fume fever.	
Ingestion:	Ingestion of large doses of nickel compounds (1-3 mg/kg) has been shown to cause intestinal disorders, convulsions, and asphyxia.	
Carcinogenicity:	See Toxicological Information (Section #11)	
Potential Environmental Effects:	POTENTIAL ENVIRONMENTAL EFFECTS: None known. Product has not been tested for environmental properties.	
Signs/Symptoms:	Metal fume fever - metallic taste in mouth, dryness, and irritation of the throat, and influenza-like symptoms. The effects may be delayed. Nickel overexposure - effects on nasal sinuses, including inflammation and ulceration.	
Target Organs:	Upper respiratory tract, eyes, skin	
Aggravation of Pre-Existing Conditions:	Exposure to fumes or dust may aggravate existing respiratory disease or dermatitis.	

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixtures:</u> Chemical Name	CAS#	Ingredient Percent	EC Num.
Aluminum	7429-90-5	4.5 - 6.5% by Mole	231-072-3
Nickel	7440-02-0	2 - 2.25% by Mole	231-111-4
Copper	7440-50-8	88.4 - 93% by Mole	231-159-6

SECTION 4 : FIRST AID MEASURES

Description of necessary measures:

Eye Contact:	Flush with water for at least 15 minutes.
Skin Contact:	Wash with soap and water.
Inhalation:	If exposed to excessive levels of metal fumes, remove to fresh air. Seek medical attention.

SECTION 5 : FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:	
--	--

Suitable Extinguishing Media:	Use extinguishing media appropriate to the surrounding material.
Fire Fighting Instructions:	Copper alloy products in the solid state present no fire or explosion hazard, but may react with strong acids, bases, or oxidizing agents.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up:

Spill Cleanup Measures: STEPS TO BE TAKEN IN THE EVENT OF SPILLS, LEAKS, OR RELEASES: Not applicable

SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:

Handling:

In welding, precautions should be taken for airborne contaminants that may originate from components of the welding rod.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

EXPOSORE GOIDLEINES.	
<u>Aluminum</u> :	
Guideline ACGIH:	TLV-TWA: 1 mg/m3 Respirable fraction (R) TLV-TWA: 1 mg/m3 Respirable fraction (R) TLV-TWA: 1 mg/m3 (R)
Guideline OSHA:	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)
Nickel:	
Guideline ACGIH:	TLV-TWA: 1.5 mg/m3 Inhalable fraction (I)
Guideline OSHA:	PEL-TWA: 1 mg/m3 PEL-TWA: 1 mg/m3 PEL-TWA: 1 mg/m3
Copper:	
Guideline ACGIH:	TLV-TWA: 1 mg/m3 TLV-TWA: 0.2 mg/m3
Guideline OSHA:	PEL-TWA: 1 mg/m3 PEL-TWA: 0.1 mg/m3
Appropriate engineering controls:	
Engineering Controls:	Local exhaust ventilation should be utilized when welding, burning, sawing, brazing, grinding, or machining when exposure exceeds occupational exposure limits.
Individual protection measures:	
Eye/Face Protection:	Safety glasses or goggles should be utilized as required by exposure. Other protective equipment should be utilized as required by welding standards.
Skin Protection Description:	Wear appropriate personal protective clothing to prevent skin contact with copper dusts and mists.
Respiratory Protection:	NIOSH-approved dust or fume respirator should be used to avoid excessive inhalation of particulates when exposure exceeds occupational exposure limits.
Other Protective:	OTHER PREVENTIVE MEASURES: Do not eat, drink, or smoke during work. Wash hands before eating or smoking.

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State:	Solid APPEARANCE: Lustrous metal
Color:	Salmon-colored
Odor:	None
Melting Point:	Not Available
Density:	LB/IN3: Not available
Specific Gravity:	Not Available

Vapor Density:	(Air = 1): Not applicable
Vapor Pressure:	Not Applicable
Percent Volatile:	Not Applicable
Evaporation Rate:	Not Applicable
pH:	Not Applicable
Flash Point:	Not Applicable
Lower Flammable/Explosive Limit:	(%): None
Upper Flammable/Explosive Limit:	(%): None
Auto Ignition Temperature:	Not Applicable

SECTION 10 : STABILITY and REACTIVITY

Reactivity:	
Reactivity:	Possibility of Hazardous Reactions: Will not occur
Chemical Stability:	
Chemical Stability:	Stable
Conditions To Avoid:	
Conditions to Avoid:	None
Incompatible Materials:	
Incompatible Materials:	Mercury, ammonia, acetylene acids. Contact with strong acids, bases, or oxidizing agents
Hazardous Decomposition Products	<u>.</u>
Special Decomposition Products:	Metallic dust or fumes may be produced during welding, burning, grinding, and machining.

SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:	
Nickel:	
Acute Toxicity:	LD50: 250 mg/kg (rodent, intraperitoneal)
<u>Copper</u> :	
Acute Toxicity:	LD50: 0.07 mg/kg (mouse, intraperitoneal)
<u>Aluminum</u> :	
ACGIH:	No
IARC:	No
NTP:	No
Nickel:	
ACGIH:	No
IARC:	Yes
NTP:	Yes
<u>Copper</u> :	
ACGIH:	No
IARC:	No
NTP:	No
Chronic Effects:	Chronic overexposure to aluminum-containing dusts may cause fibrosis of the lungs. Repeated or prolonged overexposure to copper fume may cause the skin and hair to change color. Hypersensitivity to nickel is common and may cause allergic contact dermatitis, pulmonary asthma, and conjunctivitis.
<u>Aluminum</u> :	
Inhalation:	TCLo: 4 mg/m3 /1 year (human, inhalation-respiratory and metabolic effects)
<u>Copper</u> :	
Ingestion:	TDLo: 120 µg/kg (human, oral-gastrointestinal effects)

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity:

Not Applicable

SECTION 13 : DISPOSAL CONSIDERATIONS	
BRONZE ALLOYS XP55, C61550, C69300, C66540	226999
Revision: 09/09/2015	Page 3 of 4
	Pogo 3 of 4

Description of waste:

Waste Disposal:

According to local, state, and federal regulations.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Not restricted as a dangerous good.
DOT UN Number:	Not restricted as a dangerous good.

SECTION 15 : REGULATORY INFORMATION

 $\underline{Safety, \ health \ and \ environmental \ regulations \ specific \ for \ the \ product:}$

<u>Aluminum</u> :	
TSCA Inventory Status:	Listed
Section 313:	EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.
Canada DSL:	Listed
EC Number:	231-072-3
Nickel :	
TSCA Inventory Status:	Listed
Section 313:	EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.
California PROP 65:	Listed: cancer.
Canada DSL:	Listed
EC Number:	231-111-4
<u>Copper</u> :	
TSCA Inventory Status:	Listed
Section 313:	EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.
Canada DSL:	Listed
EC Number:	231-159-6

SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:

SDS Creation Date:	December 15, 2004
SDS Revision Date:	September 09, 2015
Disclaimer:	Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

 ${\tt Copyright} \circledast$ 1996-2015 Actio Corporation. All Rights Reserved.